

Safety Certification Form

Vehicle

License No

Event	Date	Vehicle	License No
Form 2022.03 (updated March,	2022)		
Any	-	tact Trail Ride Comm. (
	(* see notes a	t bottom of form for more detail	ls)
o First Aid Kit	o No Fluid	Drips	Liability Insurance *
o Fire Extinguisher	o Battery S	Secure	GMRS Radio
o Proper Recovery Strap *	o Lights-H	ead, Tail & Brake	Secured Antenna *
o Proper Clevis, if Equipped *	o Safe Suspension		Brake Pedal Pressure
o Recovery Point Front *	o Loose Objects Secured		Front and Rear Brakes
o Recovery Point Rear *	o All Lug Nuts Present		Emergency Brake
o No Trailer Ball in Hitch *	o Spare Tire, Jack & Wrench		No Pinion Brakes *
o No Improper Lift Blocks *	o Spare Ti	re Within 3" *	Muffler
o Frame & Body Sound	o Adequate	e Roll Protection *	o Spark Arrestor *
o Drive Train Sound	o Working Seat Belts for All Passengers		o ORV Sticker or Equivalent *
o Steering Sound	o Fluid and Electrical Lines Secured		o No liquor or firearms in vehicle
official of Gear Crushers, reserv	res the right to in lous safety defic	nspect my vehicle at any ti iency. I understand that by	stand that the Trail Leader or other me for failure to meet any accepting this form Gear Crushers is
		Name of Driver (print	ed)
		Signature	Date
* Notes:	occantoble if two co	nora whaals are looked	

- Antenna: if over 48", must be sufficiently stiff or strapped down so as not to pose a danger to bystanders by swaying
- * Clevis: screw type only with proper rating. No pull pin.
- * Insurance: your vehicle must have the minimum liability insurance required by the state of registration
- * Lift blocks: no front lift blocks on leaf spring suspension, no lift blocks over 4" in rear unless OEM installed, no stacked blocks
- * Lines: fluid and electrical lines secure and not hanging below frame
- * ORV sticker: if required by regulating agency
- Pinion brakes: pinion mounted or other driveline mounted brakes, not allowed as primary braking system
- Roll protection: roll bars for open top vehicles, all roll bars made of heavy steel
- * Spare tire: diameter must be within 3" of tires on vehicle. Spare tire requirement may be waived for short distance runs. IE: "Park" type settings. Consult with trail leader. Final decision will be on a per run basis between trail leader and group members.
- * Spark arrester: not required for mufflers with offset exhaust gas flow (most stock mufflers OK)
- Recovery points: must be frame mounted tow hook (grade 5 bolts or better) or clevis, receiver hitch tow point acceptable if class III or better
- Recovery strap: No metal hooks, minimum 20,000# capacity
- * Trailer ball: use of trailer ball for recovery is not permitted! Ball must be removed or incapacitated to prevent use as recovery point.